

I'm not robot!





### COMPONENT DIAGRAMS - Model 1003C

**Brick**

PART	QTY	DIMENSIONS
FB-1	5	9 X 4.5 REGULAR
FB-2	8	9 X 4.5 NOTCH
FB12	1	7.375 X 4.5 X 0.75 RIGHT
FB13	1	7.375 X 4.5 X 0.75 LEFT
FB14	1	8.75 X 5 X 2.375 RIGHT
FB15	1	8.75 X 3 X 2.375 LEFT

**Diagram Labels:** BOTTOM, BACK, LEFT

On model 1003CL, a 9 x 4.5" brick (p/n FB-2) is used in place of the grate on the bottom.

**Damper Assembly:** Includes labels for COMBUSTION CLIP, POSITIONING STOPS, Push Rod, Set Screws, Damper Blade Assembly, Damper, Damper Blade Channel, and Damper Channel. Notes indicate channels are welded to the damper.

**Outside Air Floor Ducts:** Stoves with legs may utilize an air penetration tube (p/n 85-35, 3" diameter) and outside air kit (p/n 10270). Stoves with a pedestal may utilize a floor penetration duct (p/n 78-35).

**1003CL:** Shows a stove on a pedestal with a 3" floor duct p/n 85-35. Note: Flue not included.

**1003C:** Shows a stove on a floor with a floor duct p/n 78-35.

P/N 78-35 dimensions - 5 1/4" square (floor penetration), 11 1/2" height. Top flange - 6 3/4" square.

Page 24

